

TECHNICAL DATA SHEET
 DATASHEET 4223, Rev-



ZENER 5W VOLTAGE REGULATOR

- All ratings are @ $T_c = 25^\circ\text{C}$ unless otherwise specified.
- Operating temperature: -55°C to $+175^\circ\text{C}$ and storage temperature: -65°C to $+175^\circ\text{C}$

MAXIMUM RATINGS / ELECTRICAL CHARACTERISTICS	SYMBOL	VALUE	UNITS
MIN ZENER VOLTAGE	Min V_Z	44.7	Vdc
MAX ZENER VOLTAGE	Max V_Z	49.3	Vdc
TEST CURRENT	I_Z	25	mAmps dc
MAXIMUM IMPEDANCE @ I_Z	Max Z_Z	25	ohm
REVERSE VOLTAGE	V_R	35.8	Vdc
MAXIMUM REVERSE CURRENT	Max I_{R1}	2.0	uAmps dc
MAXIMUM KNEE IMPEDANCE @ $I_{ZK} = 1\text{ mA}$	Max Z_K	250	ohm
MAXIMUM VOLTAGE REGULATION	Max $V_Z(\text{reg})$	3.5	Vdc
MAXIMUM TEMPERATURE COEFFICIENT *	αV_Z	0.095	%/ $^\circ\text{C}$
POWER DISSIPATION *	Power	5	Watts

* Adequate energy absorption should be provided.

MECHANICAL DIMENSIONS: In Inches (mm)



MIL-PRF	CHIP	DIMENSIONS – INCHES (MILIMETERS)					
		A		B		C	
		MIN.	MAX.	MIN.	MAX.	MIN.	MAX.
MIL-PRF-19500/356F	1C4958 to 1C4989	0.087 (2.21)	0.091 (2.31)	0.069 (1.75)	0.075 (1.91)	0.0095 (0.24)	0.0105 (0.27)

TECHNICAL DATA

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.