

TECHNICAL DATA
DATA SHEET 4964, REV. -

HERMETIC POWER MOSFET N-CHANNEL

FEATURES:

- 1000 Volt, 6A, 2 Ohm, MOSFET
- Isolated Hermetic Metal Package
- Fast intrinsic Rectifier
- Low $R_{DS(on)}$
- Ceramic Seals with Glidcop leads (SHDG225509)

MAXIMUM RATINGS

ALL RATINGS ARE AT $T_c = 25^\circ\text{C}$ UNLESS OTHERWISE SPECIFIED.

RATING	SYMBOL	MIN.	TYP.	MAX.	UNITS
GATE TO SOURCE VOLTAGE	V_{GS}	-	-	± 20	Volts
ON-STATE DRAIN CURRENT @ $T_c = 25^\circ\text{C}$	$I_{D(on)}$	-	-	6	Amps
PULSED DRAIN CURRENT @ $T_c = 25^\circ\text{C}$	I_{DM}	-	-	± 24	Amps
OPERATING AND STORAGE TEMPERATURE	T_{OP}/T_{STG}	-55	-	+150	$^\circ\text{C}$
THERMAL RESISTANCE, JUNCTION TO CASE	R_{thJC}	-	-	0.72	$^\circ\text{C}/\text{W}$
TOTAL DEVICE DISSIPATION @ $T_c = 25^\circ\text{C}$	P_D	-	-	150	Watts

ELECTRICAL CHARACTERISTICS

RATING	SYMBOL	MIN.	TYP.	MAX.	UNITS
DRAIN TO SOURCE BREAKDOWN VOLTAGE $V_{GS} = 0\text{V}, I_D = 1\text{mA}$	BV_{DSS}	1000	-	-	Volts
STATIC DRAIN TO SOURCE ON STATE RESISTANCE $V_{GS} = 10\text{V}, I_D = 3\text{A}$	$R_{DS(ON)}$	-	-	2.0	Ω
GATE THRESHOLD VOLTAGE $V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	$V_{GS(th)}$	2.0	-	4.5	Volts
FORWARD TRANSCONDUCTANCE $V_{DS} = 10\text{V}, I_D = 3\text{A}$	g_{fs}	-	6	-	$\text{S}(1/\Omega)$
ZERO GATE VOLTAGE DRAIN CURRENT $V_{DS} = 0.8 \times \text{Max. Rating}, V_{GS} = 0\text{V}$ $V_{DS} = 0.8 \times \text{Max. Rating}, V_{GS} = 0\text{V}, T_J = 125^\circ\text{C}$	I_{DSS}	-	-	250 1.0	μA mA
GATE TO SOURCE LEAKAGE FORWARD $V_{GS} = 20\text{V}$	I_{GSS}	-	-	100	nA
GATE TO SOURCE LEAKAGE REVERSE $V_{GS} = -20\text{V}$				-100	
TURN ON DELAY TIME RISE TIME TURN OFF DELAY TIME FALL TIME $V_{DS} = 500\text{V}, I_D = 3\text{A}, R_G = 4.7\Omega, V_{GS} = 10\text{V}$	$t_{d(ON)}$ t_r $t_{d(OFF)}$ t_f	-	35 40 100 60	-	nsec
DIODE FORWARD VOLTAGE $T_c = 25^\circ\text{C}, I_S = 6\text{A}, V_{GS} = 0\text{V}$	V_{SD}	-	-	1.5	Volts
REVERSE RECOVERY TIME $T_J = 25^\circ\text{C}, I_F = 6\text{A}, -di/dt = 100\text{A}/\mu\text{sec}, V_R = 100\text{V}$	t_{rr}	-	-	250	nsec
INPUT CAPACITANCE OUTPUT CAPACITANCE REVERSE TRANSFER CAPACITANCE $V_{GS} = 0\text{V}, V_{DS} = 25\text{V}, f = 1.0\text{MHz}$	C_{iss} C_{oss} C_{rss}	-	2600 180 45	-	pF

