

TECHNICAL DATA  
DATA SHEET 5554, REV -

**10A, 200V HYPERFAST RECOVERY RECTIFIER**

- *Ultra-fast reverse recovery: 30ns*
- *Hermetically sealed power package*
- *MIL-PRF-19500 screening and QCI available (see part ordering information)*

**ELECTRICAL CHARACTERISTICS:**

All ratings are at  $T_A = 25^\circ\text{C}$  unless otherwise specified.

RATING	CONDITIONS	MIN	TYP	MAX	UNIT
Working Peak Reverse Voltage ( $V_{RWM}$ )	$I_R = 100 \mu\text{A}$	210	-	-	V
Average Rectified Output Current ( $I_o$ )	$T_C = 100^\circ\text{C}$	-	-	10	A
Surge Peak Forward Current ( $I_{FSM}$ ) @ $T_A=25^\circ\text{C}$	$t_p = 8.3 \text{ ms}$ , Half Sine Wave, superimposed on rated $I_o$	-	-	350	A
Thermal Resistance ( $R_{\theta JC}$ )		-	-	4.5	$^\circ\text{C/W}$
Junction Temperature ( $T_J$ )	-	-65	-	+175	$^\circ\text{C}$
Storage Temp. ( $T_{stg}$ )	-	-65	-	+175	$^\circ\text{C}$


CHARACTERISTIC	CONDITIONS	MIN	TYP	MAX	UNIT
Maximum Forward Voltage ( $V_{F1}$ )	$I_F = 6.0\text{A}$	-	-	0.90	V
( $V_{F2}$ )	$I_F = 10.0\text{A}$			0.95	
( $V_{F3}$ )	$I_F = 20.0\text{A}$			1.05	
( $V_{F4}$ )	$I_F = 6.0\text{A}$ , $T_A = 125^\circ\text{C}$			0.85	
( $V_{F5}$ )	$I_F = 6.0\text{A}$ , $T_A = 150^\circ\text{C}$			0.78	
( $V_{F6}$ )	$I_F = 6.0\text{A}$ , $T_A = -55^\circ\text{C}$			1.05	
Maximum Reverse Leakage Current $I_{RM}$ @ $V_{RWM}$	$T_A = 25^\circ\text{C}$ ( $I_{R1}$ )	-	-	1	$\mu\text{A}$
	$T_A = 125^\circ\text{C}$ ( $I_{R2}$ )			100	
	$T_A = 150^\circ\text{C}$ ( $I_{R3}$ )			500	
Breakdown Voltage ( $BV_R$ )	$I_R = 100\mu\text{A}$	210	-	-	V
Junction Capacitance ( $C_J$ )	$V_R = 10\text{Vdc}$ , $f = 1\text{MHz}$	-	-	105	pF
Reverse Recovery Tim ( $t_{RR}$ )	$I_F = 1\text{A}$ , $I_R = 1\text{A}$ , $I_{RR} = 0.1\text{A}$	-	-	30	ns

# SENSITRON SEMICONDUCTOR

**1N7068DP**  
**HERMETIC HYPERFAST  
RECOVERY RECTIFIER**

TECHNICAL DATA  
DATA SHEET 5554, REV -

**PACKAGE DIMENSIONS:**



**PART ORDERING INFORMATION:**

**1N7068DP XX X**

Part Number

**Screening Level (blank is no screening):**

Suffix	Screened in Accordance with:
blank	No screening level
SX	MIL-PRF-19500, TX Level
SV	MIL-PRF-19500, TXV Level
SS	MIL-PRF-19500, S Level

**QCI (blank is no QCI):**

Suffix	Inspection
blank	No QCI
Q	MIL-PRF-19500 QCI

# **SENSITRON**

---

## **SEMICONDUCTOR**

1N7068DP

**HERMETIC HYPERFAST  
RECOVERY RECTIFIER**

### **TECHNICAL DATA DATA SHEET 5554, REV -**

#### **DISCLAIMER:**

1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).

2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.

3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.

4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.

5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.

6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.

7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.